



Mirror Heating Panels

Technical Data

Sizes Available	Power Usage Watts @ 230v +/-10%	Recommended Heating Area ca. m ³ *Subject	Weight 10mm Aluminium Framed Models
600mm x 400mm	200	1.0 - 9.0	ca. 5 Kg
700mm x 600mm	400	9.1 - 14.5	ca. 7 Kg
900mm x 600mm	500	14.6 - 21.8	ca. 10 Kg
1100mm x 600mm	600	21.9 - 25.9	ca. 12 Kg
1200mm x 600mm	700	26.0 - 34.0	ca. 13 Kg

* Subject to the overall insulation value of the building including Glazing

Glass Surface: Mirrored Toughened Safety Glass
 Toughening Standard: EN 12150
 IPX Rating: 4
 Voltage: 230v/240v – 3 Amps
 Surface Temperature: 85° (Approximated) – Safety Cut-Off

Mounting: Wall / Ceiling / Freestanding
 Landscape or Portrait
 Models: Framed / Slim line Frameless

Mirror Options: Plain / Etched Patterned

Frame Options: 10mm Brushed Aluminium
 22mm Brushed Aluminium
 10mm White PPC Aluminium
 30mm Solid Beech Wood
 30mm Solid Oak
 Slim line Frameless (excludes 1200 x 600)

Thermostat Controls: Plug-In Thermostat Adaptor
 ThermoNomic T1
 ThermoNomic T2
 ThermoNomic T3

